

100 Micron
Polypropylene
Felt Bag

BAG FILTERS

SPECIFICATIONS

MODEL	MAXIMUM RATED FLOW (GPM)	CONNECTION SIZE	CONNECTION TYPE	BAG SIZE	NUMBER OF BAGS
BF-25	25	1 1/2	NPT	4	1
BF-50	50	2"	NPT	4	1
BF-120	120	3"	NPT	2	1
BF-300	300	4"	Flanged	2	2
BF-405	405	4"	Flanged	2	3
BF-600	600	6"	Flanged	2	4



ADVANTAGE Bag Filter vessels are constructed of heavy duty carbon steel (stainless steel is optional) with a 304 stainless steel perforated basket. The vessel is rated at 150 PSI. A 'Bura N' gasket is used to seal the lid.

ADVANTAGE bag filter vessels and systems include a 100 micron polypropylene felt bag. Polypropylene felt filter bags are available in 5, 10, 25, 50 and 100 micron sizes. Other micron ratings are available in different material types.

The **BF-25**, **BF-50** and **BF-120** can be supplied with a dedicated filter pump. When the pump is supplied, the system is skid mounted and includes a pump motor starter and system valves.

Information on all ADVANTAGE water system products is available on our website at:

www.AdvantageEngineering.com

